

SAFETY DATA SHEET

PRODUCTS RELATED TO THIS MSDS (ARCH – WIRE – SPRING)

SUPERELASTIC

THERMAL

LINGUAL

3 FORCES

REVERSE

7S TWISTED

SPOOLED (SPRING)

DISTALIZING (SPRING)

IDENTIFICATION OF THE MATERIAL

Chemical Nature, Sales Name, Use: Metal Alloy - Nickel-base Alloy.

CHEMICAL COMPOSITION

		CAS #	Exposure Limit (OSHA) in mg/m ³	Threshold Limit Value in mg/m ³
Up to	55% of Ni	7440-02-0	5*	10'
Up To	Balance of Ti	7440-32-6	5*	10'

* = respirable fraction of dust

' = exposure limits for metal or insoluble metal oxide of the metal

PHYSICAL - CHEMICAL PROPERTIES AND FLAMMABILITY

Appearance	Solid	Color	Metallic-grey
Odor	Odorless	Safety Data	None
Ph-value	None		
<i>Change of status</i>			
Bowling point	n.a.	Melting point	1371 – 1482 °C
Combustion rate	n.a.	Flammability	Not ignitable
Extinguishing Media	Sand, dolomite, graphite powder or sodium chloride work best.	Auto-ignition temperature	n.a.
Comburent capability	n.a.	Explosion limit	n.a.
Vapor pressure	n.a.	Density at 20°	n.a.
<i>Solubility and scattering features</i>			
Soluble in water	Insoluble	Soluble in fat	Insoluble
Scattering coefficient	None		

ORTHODONTIC MANUFACTURER SIA SRL

Sede Legale: Via Aristide Leonori,113 - 00147 Roma **Uffici e Stabilimento:** Zona Ind.le snc - 81050 Rocca d'Evandro (CE) Italy
Recapiti: Tel: +39 (0)823 908029 Fax: +39 (0)823 908028 **Email:** info@siaorthodontics.com - www.siaorthodontics.com

REACTIVITY

⇒ **Stability and reactivity:** stable and not reactive

THERMAL ACTIVATION MODULE

⇒ **Thermal wire:** activation starts from 30°C – 35°C

SPECIAL PROTECTION INFORMATION

Nitinol alloys in the form shipped require no special protection for handling. For specific processing, the following should be observed:

FIRST AID MEASURES

Inhalation: Use local ventilation and/or respiratory protective equipment to limit exposure to airborne dusts. If sudden overexposure does occur: remove victim to fresh air, begin artificial respiration, if victim is not breathing.

Skin contact: Exposure or repeated contact may irritate the skin. Avoid frequent and prolonged contact. Wear suitable protective clothing and gloves. In case of contact: brush off skin and clothing. Wash with soap and water. Remove metallic particles and cleanse wounds

Ingestion: Seek prompt medical help.

Eyes: Flush eyes with water.

HAZARDS IDENTIFICATION

Information on toxicity: Product tested for bio-compatibility with results concluding negative toxicological reaction.

Although Nitinol alloys do not constitute a physical or health hazard in the form sold, subsequent operations such as abrading, melting, welding, cutting or processing in any other fashion may produce potentially hazardous dust or fumes which can be inhaled, swallowed, or come into contact with skin or eyes.

CAUTION: The product may be sterilized by autoclave, and to be used from professional personnel only. *It contains Nickel, if a patient reaction is suspected, contact a physician.*

ORTHODONTIC MANUFACTURER SIA SRL

Possible hazards during the working process:

- ⇒ **Effects of overexposure:** Special protective clothing is not normally needed. Provide local exhaust ventilation in areas where metal fumes or dusts are.
- ⇒ **Primary routes of entry:** inhalation of dust and fumes.
- ⇒ **Possible cancer hazard:** Nickel is treated as a potential agent, being included in the NTP and IARC lists. Some scientific studies have found an excessive incidence of cancer of the respiratory tract among workers involved in certain steps of nickel refining processes. However, several studies on workers exposed to various forms of nickel and its compounds have not shown any increased risk of cancer.

According to the Directive 67/548/EEC all products with a minimum Nickel content of 1% are classified in the same way as suspect carcinogen (category 3) and irritating for skin. Products which these sheets refer to, have form of massive metal alloy, therefore nickel cannot develop as possible hazardous material. No toxic effects caused by the material in massive form or during the normal orthodontic practices have been noticed. A prolonged and frequent contact may cause skin irritation and other allergic reactions in subjects sensitive to nickel.

For purposes of this MSDS, occupational exposure to alloys is taken to mean dusts, fumes, or solutions containing metals that can become airborne or can spill on skin or in the eye. Occupational exposure to alloys does not include solid products (i.e. ingots or castings), provided no particle generating operations, such as grinding or cutting, occur. In most industrial situations, the significant routes of exposure would include inhalation, skin and eye contact. Titanium metal is considered relatively nontoxic.

DISPOSAL CONSIDERATION

- ⇒ **Solid forms:** Articles made of titanium are not hazardous. No special disposal regulations apply.
- ⇒ **Dusts and Fines:** If airborne, Titanium fines can burn. When ignited, titanium is very difficult to extinguish. Before being disposed of titanium fines should be stabilized (solidified or diluted with sand or other non combustible substances) to prevent being ignited. Titanium alloys can be landfilled as an industrial waste.

REGULATORY INFORMATION

- ⇒ **Hazardous:** Nitinol and Nitinol alloys are not hazardous.

ORTHODONTIC MANUFACTURER SIA SRL

Sede Legale: Via Aristide Leonori,113 - 00147 Roma **Uffici e Stabilimento:** Zona Ind.le snc - 81050 Rocca d'Evandro (CE) Italy
Recapiti: Tel: +39 (0)823 908029 Fax: +39 (0)823 908028 **Email:** info@siaorthodontics.com - www.siaorthodontics.com

FURTHER INFORMATION

⇒ **General information:** The information contained herein is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. Therefore, it should not be construed as guaranteeing specific properties.



SCHEDA SICUREZZA (Medical Safety Data Sheet)

Revisione 2 Pagina 1 di 2
Rif. ISO 9002 §/ EN 46002 § 4.2
Modello 5/1 Revisione 1
Data 02/08/2018
MSDS G3-E.docx

SAFETY DATA SHEET

PRODUCTS RELATED TO THIS MSDS

COATING OF STAINLESS STEEL AND NICKEL TITANIUM ARCHWIRE

IDENTIFICATION OF THE MATERIAL

Chemical Nature, Sales Name, Use: Epoxy and Acrylic Resin coating Nickel-Base Alloy

CHEMICAL COMPOSITION

Up to 45% of Epoxy Resin
Up To Balance of Acrylic Resin

REACTIVITY

⇒ **Stability and reactivity:** stable and not reactive

SPECIAL PROTECTION INFORMATION

Epoxy and Acrylic Resin coating Nickel-Base Alloys in the form shipped require no special protection for handling. For specific processing, the following should be observed:

FIRE REMOTENESS REQUIREMENT: General-Recommended.

SPECIAL PRECAUTIONS: Use good housekeeping practices to prevent accumulation of dust, to keep airborne dust wire shards or scrap wire at a minimum. The information set forth on this MSDS is believed to be accurate and represents the best information currently available to SIA Orthodontic Manufacturer. However, SIA Orthodontic Manufacturer makes no representation or warranties regarding the accuracy or completeness of the information and assumes no liability for any loss, damage, cost, or expense that may arise out of the use of, or reliance on the information by any person. Users should make their own investigations to determine the suitability of the information for their particular purpose.

FIRST AID MEASURES

Inhalation: Use local ventilation and/or respiratory protective equipment to limit exposure to airborne dusts.

Skin contact: Exposure or repeated contact may irritate the skin. Avoid frequent and prolonged contact. Wash with soap and water.

Ingestion: if large amount is swallowed, get medical attention.

Eyes: Flush eyes with water.

ORTHODONTIC MANUFACTURER SIA SRL

Sede Legale: Via Aristide Leonori,113 - 00147 Roma **Uffici e Stabilimento:** Zona Ind.le snc - 81050 Rocca d'Evandro (CE) Italy
Recapiti: Tel: +39 (0)823 908029 Fax: +39 (0)823 908028 **Email:** info@siaorthodontics.com - www.siaorthodontics.com

SAFETY DATA SHEET

FIRE FIGHTING MEASURES:

Flash point: N/A Flammable limits: Upper explosive limit (uel)% : N/A Lower explosive limit (lel) (%): N/A Extinguishing media: In finish form, parts are not combustible Special fire fighting procedures: None

HAZARDS IDENTIFICATION

Information on toxicity: Product tested for bio-compatibility with results concluding negative toxicological reaction. Although Epoxy and Acrylic Resin coatings do not constitute a physical or health hazard in the form sold, subsequent operations such as abrading, cutting or processing in any other fashion may produce potentially hazardous dust or fragments which can be inhaled, swallowed, or come into contact with skin or eyes.

CAUTION: The product may be sterilized by autoclave, and to be used from professional personnel only. *If a patient reaction is suspected, contact a physician.*

TOXICOLOGICAL INFORMATION: None

ECOLOGICAL INFORMATION: None

SPILL OR LEAK PROCEDURE STEP TO BE TAKEN IN CASE MATERIAL IS LEAKED OR SPILLED: Fine material should be swept or vacuumed. Avoid using compressed air to maneuver spills or leaks of dusty material as this may likely cause eye contamination.

DISPOSAL CONSIDERATION: Dispose of in accordance with applicable federal, state, and local regulations. **NOTE:** TREAT USED ARCHES AS BIOHAZARDOUS WASTE.

REGULATORY INFORMATION

⇒ **Hazardous:** Nitinol and Nitinol alloys are not hazardous.

FURTHER INFORMATION

⇒ **General information:** The information contained herein is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. Therefore, it should not be construed as guaranteeing specific properties.